



" The Innovator in American Made Casters, Wheels, Bumpers, Couplers, and Conveyor Systems "



Proudly Introduces:



LevelMaster 2"

(Dual Wheel Industrial)

LevelMaster 2" is the latest new product solution from Darnell-Rose, the innovator in high quality American made casters. This adjustable leveling caster is designed to move business machines such as Computer Frames, Electronic Enclosures, Copy Machines, Server Cabinets, Display Racks or Kiosks into place, while also providing the capability of leveling and stabilizing to assure a sound foundation especially on uneven floor surfaces. Just mount it, roll it in place, and level it off to provide rock solid security for your most valuable assets.

Modeled after our robust 30 Series swivel yoke, the Darnell-Rose LevelMaster 2" is designed and engineered so that each caster can easily handle a maximum load up to 400 lbs. Available in either plate or stem mounted options, the LevelMaster 2" also features a shock absorbing non-slip rubber leveling pad for improved stability when engaged with floor surfaces.



World class quality, unmatched performance, and over 90 years of providing solutions for your mobility needs is the reason you should put your trust into Darnell-Rose casters, wheels, rubber bumpers, industrial truck couplers, and conveyor systems.



" The Innovator in American Made Casters, Wheels, Bumpers, Couplers, and Conveyor Systems "



Proudly Introduces:



LevelMaster 2”

(Dual Wheel Industrial)

Quality Features

- **FOUR-SIDED, DOUBLE BALL RACEWAY.**

Hardened steel ball bearings in the load bearing and secondary thrust bearings touch the swivel raceway “on all four sides.” This protects the king pin from shock loading for free swiveling under heavy loads.

- **HEAT-TREATED MOVING PARTS.**

All moving parts are heat treated to a precise molecular depth and Rockwell hardness. This extends caster life under rugged conditions and shock loads.

Options

- Maintenance Free Swivel Bearings
- Conductive or Static-Dissipative Wheels
- Gray, Non-Marking Wheels
- Powder Coated or Black Oxide Finishes



Wheel Diameter	Tread Width	Load Capacity	Wheel Material	Bearing	Swivel Part Number	Approx. Weight	Overall Height	Swivel Radius
2	7/8	250	Round Doughnut / Neoprene	Ball	32-20-XDN-RD-LM	2 1/2	3 1/4	3 1/8
			Neoprene Rubber	Ball	32-20-XDN-LM			
			Hard Rubber	Ball	32-20-XH-LM			
		300	Hi-Cap Neoprene	Ball	32-20-XKN-LM			
		400	Advanced Elastomer	Ball	32-20-XAE-LM			